

## DC 24V 2.5A UPS Din Rail

Model No.: DR024060-02B

INPUT	Voltage Range	190 - 240VAC	
	Frequency Range	50 - 60Hz	
OUTPUT	Voltage (AC Mode)	24-28V $\pm$ 2%	
	Voltage (Battery Mode)	Same as battery voltage	
	Rated Current	2.5A	
	Rated Power (Max.)	70W (with maximum 1A charging current)	
	Efficiency (Typ.)	>86%	
	Ripple & Noise	<120mVp-p	
	Output Channel	2 Channels	
CHARGING	Voltage	22-27.6V $\pm$ 2%	
	Current	500mA (max.)	
Constant voltage mode, charge current decreases when battery voltage increases.			
PROTECTION	Input	2A / 250VAC fuse	
	Overload	3A $\pm$ 5%	
		Hiccup mode, recovers automatically after fault condition is removed.	
	Over Voltage	30V $\pm$ 5%	
		Hiccup mode, recovers automatically after fault condition is removed.	
	Battery Low Voltage	21V $\pm$ 2%	
PSU shuts down until AC power is reconnected			
Short Circuit	Hiccup mode, recovers automatically after fault condition is removed.		
ENVIRONMENT	Temperature	Working: -20 - 45°C	Storage: -30 - 80°C
	Humidity	Working: 20 - 80%RH	Storage: 10 - 90%RH
LED INDICATOR	Green	On	AC supplies
	Red	On	Battery supplies
SAFETY & EMC	EMC Standards	EN 55022: 2010, EN 55024: 2010, EN 61000-3-2: 2014, EN 61000-3-3: 2013	
	LVD Standards	EN 60950-1: 2006 + A11: 2009 + A1: 2010 + A12: 2011 + A2: 2013	

---

<b>PLASTIC BOX &amp; PACKING</b>	<b>Default Plastic Box</b>	89.5mm x 93mm x 56mm, can pack with a 12V 7Ah Lead Acid battery externally
	<b>Packing</b>	