

DC 24V 2.5A Din Rail

Model No.: DR24060-02C

INPUT	Voltage Range	190 - 240VAC	
	Frequency Range	50 - 60Hz	
OUTPUT	Voltage (AC Mode)	24-28V \pm 2%	
	Rated Current	2.5A	
	Rated Power (Max.)	70W	
	Efficiency (Typ.)	>86%	
	Ripple & Noise	<120mVp-p	
	Output Channel	2 Channels	
PROTECTION	Input	2A / 250VAC fuse	
	Overload	3A \pm 5%	
		Hiccup mode, recovers automatically after fault condition is removed.	
	Over Voltage	30V \pm 5%	
		Hiccup mode, recovers automatically after fault condition is removed.	
PSU shuts down until AC power is reconnected			
Short Circuit	Hiccup mode, recovers automatically after fault condition is removed.		
ENVIRONMENT	Temperature	Working: -20 - 45°C	Storage: -30 - 80°C
	Humidity	Working: 20 - 80%RH	Storage: 10 - 90%RH
LED INDICATOR	Green	On	DC OK
SAFETY & EMC	EMC Standards	EN 55022: 2010, EN 55024: 2010, EN 61000-3-2: 2014, EN 61000-3-3: 2013	
	LVD Standards	EN 60950-1: 2006 + A11: 2009 + A1: 2010 + A12: 2011 + A2: 2013	
PLASTIC BOX & PACKING	Default Plastic Box	89.5mm x 93mm x 56mm, can pack with a 12V 7Ah Lead Acid battery externally	
	Packing		